


Specification

Linear lighting system

LR5535(A)




LR5535(A)




Features

- Several optional diffuser: general PC diffuser, flexible PC diffuser, flexible anti-glare diffuser, black diffuser, aluminium blind diffuser
- 50mm large luminous surface , rimless recessed design, integrated into architecture.
- Leakage proof shield design, perfect details.
- AL6063-T5 aluminum profile with high-quality surface treatment, black, white and silver are optional.
- Multiple optional connectors : 180 ° direct connection, L type, T type, X type




Details




Standard Configuration

Picture	Item	Parameter
	①Profile	Profile weight : 2.52kg/2.5m Size : L2500*W95*H35mm Material : AL6063-T5 Surface processing : Anodizing
	②Cover	Type: Frosted diffuser Material : PC Light transmittance : 75% Size : L2500*W48.8*H5.6mm PC Feature : The diffuser will extend (shrink) 0.8mm/m when the temperature raises (drops) 10°C.
	③End cap	Model : EC-LR5535(A)FSS Size : L55*W35*H22mm
	④Cable clip	BG-03
	⑤Install screw	Model : CL-01 Size : M3.5*40mm

Optional Accessories

Picture	Item	Parameter
	⑤Flexible strip D8280-24V-34mm	Material : FPC,CCT:1900/2300/2700/3000/3500/4000/5000/6000K ; CRI > 80/>95 ;Voltage :24V ;Power : 25W/m ;Lumen :3250Lm/m ; Width : 34mm ; Minimum cutting unit : 28LEDs/50mm ;
	⑤Flexible strip D8560SWW-24V-34mm	Material : FPC , CCT : 2700-6000K ; CRI > 80/>95 ; Voltage : 24V ; Power : 25W/m ; Lumen : 2740Lm/m ; Width : 34mm ; Minimum cutting unit : 28LEDs/50mm ; tunable white
	⑤Rigid modular DY8280-24V-36mm	Material : FR4,CCT:1900/2300/2700/3000/3500/4000/5000/6000K ; CRI > 80/>95 ;Voltage :24V ;Power : 25W/m ;Lumen :3250Lm/m ; Width : 36mm ; Minimum cutting unit : 28LEDs/50mm ;
	⑤Rigid modular DY8560SWW-24V-36mm	Material : FR4 , CCT : 2700-6000K ; CRI > 80/>95 ; Voltage : 24V ; Power : 25W/m ; Lumen : 2740Lm/m ; Width : 36mm ; Minimum cutting unit : 28LEDs/50mm ; tunable white
	⑧Power supply	Model : BSD-V24-065S Size : L346*W30*H23.5mm
	Reflective paper	Model : BG-14 Size : L15000*W19*H0.188mm

Cover type

Picture	Item	Parameter
	②cover	Type: Diffuse flexible mask Material: PC + silica gel Transparency: 70% Size: L50000*W48.8*H5.6mm
	②cover	Type: Aluminum mask Material: Aluminum alloy Size: L2500*W48.8*H5.6mm
	②cover	Type: Night mask Material: PC Transparency: 15 % Size: L2500*W48.8*H5.6mm



Corner fittings

EX-17	EX-E6 (7-type 120°)	EX-E7 (7-type 60°)	EX-E8 (L-type 120°)
EX-E9 (Y-type 120°)	EX-E10 (L-type 60°)	EX-E11 (X-type 60°+120°)	EX-E12 (T-type 60°+120°)

Optical Parameter


D8280-24V-34mm light source, frosted diffuser

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




Package

Mode 1 :



Mode 2 :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	2560*99*61mm	2.76	3.26	1pcs/box
Whole bundle	Hat box	2580*228*207mm	16.56	19.56	6pcs/box
Whole box packaging	Paper box	2580*182*169mm	22.08	25.08	8pcs/box